



DP2150-M

< FireKing® Mixed Media Safe

Two safes in one – the ultimate in versatile protection. The top section holds paper records and files, while the bottom section holds media.

Media Compartment Optional Interiors

CM19-FS Fixed shelf

CM19-CD Composite Drawer

Paper Compartment Optional Interiors

S-21 Fixed shelf



1-hr
fire rated



theft
resistant



3-hr -
125° rating



water
resistant



Made in the
U.S.A.

Model No.	Inside Dimensions H x W x D	Outside Dimensions H x W x D	Approx. Shipping Wt.	Capacity
FireKing® 3-Hour Fire with Impact Rated Data Safes*				
DM1413-3	13 ⁵ / ₈ " x 11 ¹ / ₂ " x 16 ¹ / ₁₆ "	29 ⁵ / ₈ " x 25 ¹ / ₄ " x 31"	650 lbs.	1.5 cu. ft.
DM2513-3	24 ⁵ / ₁₆ " x 11 ¹ / ₂ " x 16 ¹ / ₁₆ "	40 ¹ / ₄ " x 25 ¹ / ₄ " x 31"	740 lbs.	2.7 cu. ft.
DM2520-3	24 ⁵ / ₁₆ " x 18 ⁵ / ₈ " x 16 ¹ / ₁₆ "	40 ¹ / ₄ " x 32 ¹ / ₁₆ " x 31"	1,050 lbs.	4.5 cu. ft.
DM3420-3	33 ¹ / ₈ " x 18 ⁵ / ₈ " x 16 ¹ / ₁₆ "	49 ¹ / ₁₆ " x 32 ¹ / ₁₆ " x 31"	1,240 lbs.	6.0 cu. ft.
DM4420-3	43 ⁵ / ₈ " x 18 ⁵ / ₈ " x 16 ¹ / ₁₆ "	59 ³ / ₄ " x 32 ¹ / ₁₆ " x 31"	1,420 lbs.	7.9 cu. ft.

See your dealer for the complete selection of interior designs. *Exterior depth does not include handle depth of 1⁵/₁₆".

FireKing® Mixed Media Safe*

DP2150-M		59 ³ / ₄ " x 32 ¹ / ₁₆ " x 31"	1,290 lbs.	
Paper compartment	19 ¹ / ₂ " x 26 ³ / ₄ " x 20 ²⁹ / ₃₂ "			6.1 cu. ft.
Media compartment	24 ⁵ / ₁₆ " x 18 ⁵ / ₈ " x 16 ¹ / ₁₆ "			4.4 cu. ft.

*Limited one year warranty. Contact customer service for warranty terms and conditions.

Test Procedure

**Maintain an interior temperature less than 125°F and an interior relative humidity less than 80% for Class 125, when exposed to fire as per the Standard Time Temperature Curve for 3 hours to 1925°F. Successfully undergo all other requirements for the Fire Endurance Test, the Explosion Hazard Test and the Humidity Test.