

MAVERICK VAULT

Construction Makes The Vault


The Maverick vault is perfect for budget-minded buyers looking for great value. Its heavy 10 gauge body thickness and 3/8" door edge thickness compares to competitors' mid to upper-level safes. Its 75 min in 1200° engineered fire protection is far superior to most competitors top line.

10GA

OVERALL BODY
STEEL THICKNESS

9

LOCKING
BOLTS



DOOR STEEL THICKNESS

11GA Steel Plate
Single Fire Wall
10GA Door Shell

VAULT FEATURES

- FIRE PROTECTION1200°F In 75 Minutes
 - OVERALL BODY STEEL THICKNESS 10GA
 - DOOR EDGE STEEL THICKNESS 3/8"
 - LOCKING BOLTS 9
 - LIGHTSOptional ☒
 - DEHUMIDIFIEROptional ☒
 - DOOR ORGANIZEROptional ☒
 - HINGE CAPSOptional ☒
- Included in Bundle (Corner Bolts Unavailable for 4026 & 6026) ☒



Model	Height	Width	Overall Depth	Volume	Weight	Locking Bolts
Maverick 4024	40"	24"	18"/21"	8 Cubic Feet	430 Lbs.	9
Maverick 6024	60"	24"	18"/21"	14 Cubic Feet	580 Lbs.	9
Maverick 6026	60"	26"	20"/23"	16 Cubic Feet	620 Lbs.	9
Maverick 6031	60"	31"	27"/30"	28 Cubic Feet	805 Lbs.	9
Maverick 6041	60"	41"	27"/30"	32 Cubic Feet	990 Lbs.	9
Maverick 6637	66"	37"	27"/30"	36 Cubic Feet	1000 Lbs.	9
Maverick 7241	72"	41"	27"/30"	45 Cubic Feet	1125 Lbs.	11