

**Body & Door:** Multi-layered structure that combines outer and inner steel plates, reinforced steel bars and a monolithic casting of Alchronite, ISM's special torch and drill resistant composite material, embedding a layer of ISM's patented anti-penetration alloy grid.

**Bolts & Locking Mechanisms:** Three-way active boltwork. Double-action locking mechanism. Glass plate relocking protection on all locks.

**Locks:** Two UL approved locks. Mechanical or digital combination lock and a high security key lock.

Interior Fitting: Adjustable removable shelves. A hole for an alarm system connection - optional.

## SUPER PLATINUM TRTL-60x6

U.L. APPROVED TRTL-60X6

ISM's top of the line maximum burglary resistant security safe. SUPER PLATINUM was created as a result of ISM's conviction to create the world's best high security safe.















Model	Inside Dimensions			Outside Dimensions			Volume	Weight*	Door Swing		
iviouei	Н	W	D	Н	W	D	CuFt	Lbs	Α	В	С
SPL262316	26	23	16	36	33	30	5.5	2200	20.5	59.5	60
SPL352416	35	24	16	45	34	30	7.8	2750	21.5	60.5	62
SPL552616	55	26	16	65	36	30	13.2	3950	23.5	62.5	66
SPL652916	65	29	16	75	39	30	17.5	4700	26.5	65.5	72
SPL673623	67	36	23	77	46	37	32.1	6150	33.5	79.5	86

Shelves							
1							
2							
2							
3							
4							

## Colors:











RAL 7040 **RAL 7016** 









## Add Ons:

- Left Swing Optinal No charge
- Preparation (only) for movement time-lock No charge By Request
- Custome interior secured compartments By Request
- Additional shelves By Request







SPL-35-24-16



SPL-55-26-16



SPL-65-29-16









<sup>\*</sup> Weight Tolerance - 5%.

<sup>\*\*</sup> Dimensions Tolerance - ±0.5".

<sup>\*\*\*</sup> Add 2" to outside depth for 3-Spokes Operating Handle.

<sup>\*\*\*\*</sup> Add 3.55" to outside depth for Pull-Handle.