

COMMERCIAL SECURITY SAFES

CSC SERIES COMPOSITE SAFES



American Security CSC SERIES COMPOSITE SAFES are an affordable solution when you want to protect both documents from fire and valuables from burglary attacks. During extreme testing procedures the CSC SERIES COMPOSITE safes passed a 2-Hour, 350°F factory fire test certification.

DOOR FEATURES

- Overall thickness of 4-5/8" and is constructed with a 2" defense barrier of outer and inner steel plates creating a burglary resistant structure enclosing a unique proprietary, fire resistant material

BODY FEATURES

- 2-7/8" double wall steel construction enclosing a unique, high-density fire and burglary resistant composite material
- Durable powder coated adjustable shelves
- Removable casters provide easy delivery and installation
- Fire Endurance: 2 hour, 350°F factory fire rating. Tested at temperatures up to 1700°F
- Heat expandable intumescent door seal guards contents against severe fires

LOCKING MECHANISM FEATURES

- Two to four 1½" diameter solid steel chrome-plated locking bolts
- Two to three 1½" diameter solid steel dead bolts lock deep into body preventing door removal during a forced entry attempt
- U.L. Listed Group II combination lock with chrome-plated spy-proof dial. Optional electronic locks available
- Lock protected by a tempered glass relock device
- Heavy duty steel hinges provide easy, smooth door operation
- One internal counter-sunk anchor hole and mounting hardware are provided to securely anchor safe
- Attractively accented with a full width fascia panel and matching three point handle
- Durable and attractive charcoal gray textured finish



CSC4520

Optional Stor-It cabinets available in models CSC3018 and CSC4520. No kit needed, drawers slide right in.

Optional 8" LED light kit with motion sensor available for all models. See page 10 for details.



CSC1413



CSC1913



CSC3018

Model	Outside Dimension H" x W" x D"	Inside Dimension H" x W" x D"	Door Clearance H" x W"	Door Thickness"	Body Thickness"	Cubic Capacity	Weight	Lock Type
CSC1413	19-½ x 18 x 19-¾	14 x 12-½ x 12-¼	14 x 12-½	2	2-¾	2,135	256 lbs.	Spy-proof dial, ESL10
CSC1913	24-½ x 18 x 19-¾	19 x 12-¾ x 12	19 x 12-¾	2	2-¾	2,898	318 lbs.	Spy-proof dial, ESL10
CSC3018	35-½ x 23-½ x 24	30 x 18 x 16-½	30 x 18	2	2-¾	8,802	480 lbs.	Spy-proof dial, ESL10
CSC4520	50-½ x 25-½ x 28-¾	45 x 20 x 21-¼	45 x 20	2	2-¾	19,080	944 lbs.	Spy-proof dial, ESL10

Add 2" to outside depth for handle, dial and hinge projection. Add ¾" (casters) and 1" (rubber feet) to outside height.