

## STAR® ROUND LIFT-OUT DOOR

STAR SAFE® FLOOR SAFES are engineered with advanced security features. STAR Tube safes have been the standard for gas stations, fast food, small retail establishments and home owners for over 70 years.

### FEATURES

- Manipulation resistant, unitized key changeable lock protected by a revolving carburized hardplate
- Removable dial and drive/drill resistant spindle preventing damage from burglary attack and additional protection from hold-up

- Door, 7-¼" clear opening, is 1-¾" solid steel
- Door is securely locked by three bolts each requiring over 25,000 pounds to shear
- Each locking bolt has its own hardened steel positive relocking bolt

- Body — Heavy "B" rate construction
- Water resistant, high impact molded dust cover with rubber "O"-ring seal does not rattle or slide like most covers

**Note:** Safes with slotted doors are not recommended for overnight storage.



STAR "C" RATE  
SLOTTED ROUND DOOR  
WITH ¾" x 3 ½" SLOT



Model	Outside Dimension H" x W" x D"	Inside Dimension H" x W" x D"	Door Clearance H" x W"	Door Thickness"	Body Thickness"	Cubic Capacity	Weight	Lock Type
C3 / K3 †	8-¾ DIA x 9	8-¼ DIA x 5-¾	7-¼ DIA	1-¾	7 GA	280	40 lbs.	Combination Lock, Key Lock
C5 / K5 †	8-¾ DIA x 13-½	8-¼ DIA x 10	7-¼ DIA	1-¾	7 GA	510	48 lbs.	Combination Lock, Key Lock
C7 / K7 †	8-¾ DIA x 19	8-¼ DIA x 16	7-¼ DIA	1-¾	7 GA	785	55 lbs.	Combination Lock, Key Lock

† (K) = Key lock door

## STAR® RECTANGULAR BODY, ROUND LIFT-OUT DOOR

Star Safe® Rectangular Body, Round Lift-out Door "B" RATE FLOOR SAFES offer a large cubic inch capacity at a reasonable price. Strong, continuously welded steel bodies are offered with our standard "C" rate lift-out combination door and water-resistant dust cover.

### FEATURES:

- Utilizes the STAR high security "C" rate door



When properly installed in concrete, STAR® Floor Safes provide excellent fire and burglary protection. Now, with the water resistant dust cover, you get protection from water as well.

Model	Outside Dimension H" x W" x D"	Inside Dimension H" x W" x D"	Door Clearance H" x W"	Door Thickness"	Body Thickness"	Cubic Capacity	Weight	Lock Type
B17	13 x 13 x 15	12 x 12-½ x 10	7-¼ DIA	1-¾	4 GA	1,500	98 lbs.	Combination Lock, Key Lock
B24	13 x 13 x 19	12 x 12-½ x 14-½	7-¼ DIA	1-¾	4 GA	2,175	122 lbs.	Combination Lock, Key Lock