

TL-15 & TL-30 MONEY CHESTS

DXF U.L. LISTED



American Security TL-15 and TL-30 U.L. Listed MONEY CHESTS qualify for Mercantile & Broadform Insurance Class ER (TL-15) and F (TL-30) with a banking rating of BR (TL-15) and G (TL-30). American Security MONEY CHESTS offer the highest level of security available with many outstanding features and a wide range of options.

DOOR FEATURES

- DXF model is TL-30 constructed of 1 $\frac{3}{4}$ " thick laminated steel with a special hardened drill resistant plate
- Oil impregnated bronze bearing hinges



BODY FEATURES

- DXF models: Models under 50" in height consist of $\frac{1}{2}$ " thick steel plate with 100,000 P.S.I. minimum tensile strength. DXF models over 50" in height constructed of $\frac{3}{4}$ " thick steel plate with 75,000 P.S.I. minimum tensile strength. All external seams are beveled and continuously welded
- Shelf strips installed allowing shelf adjustment. Shelves optional

LOCKING MECHANISM FEATURES

- U.L. listed Group 2M key changeable combination lock, with relock and 1 million possible combinations
- Single auxiliary spring loaded relocking device, activated by a punching attack
- Locks and relocks protected by a patented active hardplate
- A handle activated locking mechanism consisting of two to six 1" chromed steel locking bolts
- Five boltwork sizes allow American Security to build units from 12" (10 $\frac{1}{2}$ " for DXE/DXF) to 88" high, widths from 14" to 41"
- Solid steel dead bar prevents door removal if hinges are removed during a forced entry attempt
- Compact locking mechanism and boltwork cover allow for optional door mounted coin racks

HINGE FEATURES

- Fabricated from high strength steel with precision machined alloy dowel pins
- Oil impregnated bronze bearing assures easy opening doors and reduced maintenance
- Vertical height adjustment

OPTIONAL FEATURES

- Spy proof dial
- Key lock dial
- Coin racks
- Managers lockers
- Interior lockers
- Interior drawers
- Adjustable shelves
- Electronic locks
- Auxiliary Key-Op locks
- Claddings
- Anchor bolt assembly
- Left swing door
- Internal rotary hopper
- Internal deposit slot
- Internal deposit chutes
- Hidden compartments
- Special sizes
- Custom colors

Model	Outside Dimension H" x W" x D"	Inside Dimension H" x W" x D"	Door Clearance H" x W"	Door Thickness"	Body Thickness"	Cubic Capacity	Weight	Lock Type
DXF1414	15- $\frac{1}{2}$ x 15- $\frac{1}{2}$ x 17- $\frac{3}{4}$	14- $\frac{1}{2}$ x 14- $\frac{1}{2}$ x 12	13 x 13	1- $\frac{3}{4}$	$\frac{1}{2}$	2,523 in.	357 lbs.	See pg. 52
DXF1818	19- $\frac{1}{2}$ x 19- $\frac{1}{2}$ x 17- $\frac{3}{4}$	18- $\frac{1}{2}$ x 18- $\frac{1}{2}$ x 12	17 x 16- $\frac{3}{4}$	1- $\frac{3}{4}$	$\frac{1}{2}$	4,107 in.	527 lbs.	See pg. 52
DXF2020	21- $\frac{1}{2}$ x 21- $\frac{1}{2}$ x 25- $\frac{1}{4}$	20- $\frac{1}{2}$ x 20- $\frac{1}{2}$ x 20	19 x 18- $\frac{3}{4}$	1- $\frac{3}{4}$	$\frac{1}{2}$	8,405 in.	648 lbs.	See pg. 52
DXF2420	25- $\frac{1}{2}$ x 21- $\frac{1}{2}$ x 25- $\frac{1}{4}$	24- $\frac{1}{2}$ x 20- $\frac{1}{2}$ x 20	23 x 18- $\frac{3}{4}$	1- $\frac{3}{4}$	$\frac{1}{2}$	10,045 in.	735 lbs.	See pg. 52
DXF2424XD	25- $\frac{1}{2}$ x 25- $\frac{1}{2}$ x 29- $\frac{1}{4}$	24- $\frac{1}{2}$ x 24- $\frac{1}{2}$ x 24	23 x 22- $\frac{3}{4}$	1- $\frac{3}{4}$	$\frac{1}{2}$	14,406 in.	888 lbs.	See pg. 52
DXF3018XD	31- $\frac{1}{2}$ x 19- $\frac{1}{2}$ x 25- $\frac{1}{4}$	30- $\frac{1}{2}$ x 18- $\frac{1}{2}$ x 20	28 x 16	1- $\frac{3}{4}$	$\frac{1}{2}$	11,285 in.	864 lbs.	See pg. 52
DXF3024	31- $\frac{1}{2}$ x 25- $\frac{1}{2}$ x 25- $\frac{1}{4}$	30- $\frac{1}{2}$ x 24- $\frac{1}{2}$ x 20	28 x 22	1- $\frac{3}{4}$	$\frac{1}{2}$	14,945 in.	1,039 lbs.	See pg. 52
DXF3030	31- $\frac{1}{2}$ x 31- $\frac{1}{2}$ x 25- $\frac{1}{2}$	30- $\frac{1}{2}$ x 30- $\frac{1}{2}$ x 20	28 x 28	1- $\frac{3}{4}$	$\frac{1}{2}$	18,605 in.	1,283 lbs.	See pg. 52
DXF4024	41- $\frac{1}{2}$ x 25- $\frac{1}{2}$ x 25- $\frac{1}{4}$	40- $\frac{1}{2}$ x 24- $\frac{1}{2}$ x 20	38 x 22	1- $\frac{3}{4}$	$\frac{1}{2}$	19,845 in.	1,295 lbs.	See pg. 52
DXF4524	46- $\frac{1}{2}$ x 25- $\frac{1}{2}$ x 25- $\frac{1}{4}$	45- $\frac{1}{2}$ x 24- $\frac{1}{2}$ x 20	43 x 22	1- $\frac{3}{4}$	$\frac{1}{2}$	22,295 in.	1,422 lbs.	See pg. 52
DXF5030	52 x 32 x 25- $\frac{1}{2}$	50- $\frac{1}{2}$ x 30- $\frac{1}{2}$ x 20	49- $\frac{1}{2}$ x 29	1- $\frac{3}{4}$	$\frac{3}{4}$	30,805 in.	2,036 lbs.	See pg. 52
DXF5224	54 x 26 x 25- $\frac{1}{2}$	52- $\frac{1}{2}$ x 24- $\frac{1}{2}$ x 20	51- $\frac{1}{2}$ x 23	1- $\frac{3}{4}$	$\frac{3}{4}$	25,725 in.	1,815 lbs.	See pg. 52
DXF6030	62 x 32 x 25- $\frac{1}{2}$	60- $\frac{1}{2}$ x 30- $\frac{1}{2}$ x 20	59- $\frac{1}{2}$ x 29	1- $\frac{3}{4}$	$\frac{3}{4}$	36,905 in.	2,368 lbs.	See pg. 52
DXF7234	74 x 36 x 31- $\frac{1}{2}$	72- $\frac{1}{2}$ x 34- $\frac{1}{2}$ x 26	71- $\frac{1}{2}$ x 33	1- $\frac{3}{4}$	$\frac{3}{4}$	65,033 in.	3,293 lbs.	See pg. 52

*Add 2" for dial and hinge projection. † = 1 - 9/16" anchor hole with 1/2" anchor bolt kit standard on safes under 750 lbs.