

Premium Quality You Can Trust

Visit us online at www.gardall.com

Economical Depository Safes



Front Loading Depository Safes

Single Door

- "B" rated solid 1/2" thick steel door 1/4" body
- 3 active locking bolts
- Anchoring holes for ease of installation
- Anti fish baffles
- Electronic welding for strength
- UL listed, S&G Group II combination lock
- Powder coated paint for durability

Double Door

- Solid steel locking bar to prevent door removal
- Front load style for added security and ease of deposits
- Electronic welding for strength and durability
- Powder coated paint for durability

Standard Features

- 1/2" plate steel door
- 1/4" thick body
- External re-locker
- Anti fish sawtooth baffle
- Excellent for mounting in delivery vehicles
- Mounting holes pre-drilled (4)
- Available in 3 sizes
- Laser cut door for exact fit

Model	Outsi H	de Dime W	nsions D		Insid H	le Dimen W	sions D	Door Size	Weight (lbs.)
DS1914-G-C★	19"	13½"	15"		12"	12¾"	12"	11"x11"	128
DS1914-G-K	19"	13½"	15"		12"	12¾"	12"	11"x11"	128
DS3315-G-CC★/KK	32¼"	15¾"	15¾"		10¼"	12½"	14½"	10¾"×13"	237
SDS3315-G-EE	32¼"	15¾"	15¾"		10¼"	12½"	14½"	10¾"×13"	237
DS3920-G-CC★	39"	201/4"	22"	Т	12½"	19½"	19¼"	13½"×17%"	374
				В	12½"	19½"	19¼"		