

Visit us online at www.gardall.com



Keep excess till cash locked away and out of sight to prevent loss from pilferage.

Under Counter Depository Safes – 1/2" Plate Steel Door, 1/4" Body

	Outsi	de Dimen	sions	Ins	Weight		
Model	Н	W	D	Н	W	D	(lbs.)
DS86-G-K	8"	6"	12"	7½"	5½"	11"	34
DS86-G-C	8"	6"	12"	7½"	5½"	11"	34
TC1206-G-K	12"	6½"	8"	91/4"	6"	7"	35
TC1206-G-C	12"	61/2"	8"	91/4"	6"	7"	35
DS1210-G-K	12"	8"	10"	10¼"	7½"	9"	47
DS1210-G-C	12"	8"	10"	101/4"	7½"	9"	47

Anchoring holes in bottom for easy installation



Compact Utility Safes

Designed for use in walls, basements, car trunks, and RV's. Solid steel plate with insurance "B" rated construction. This safe also features a U.L. listed Group II combination lock. Door will interchange with many other Gardall Safes. 1/2" pre-drilled mounting holes in base.

Standard Features

- 1/2" plate steel door
- Independent relock on lock
- Group II electronic lock (optional) 4 anchoring holes in bottom
- UL listed, S&G Group II combination lock

	ide Dimen	sions	In	side Dimei	nsions	Inside Cubic	Approx. Weight	
Model	Н	W	D	Н	W	D	Inches	(lbs.)
H2-G-C	11¼"	11½"	12¾"	10½"	11"	10¾"	1242	70

Add 11/2" to outside depth for dial and handle.