



**Your Best Protection
Against Robbery and Fire**

Visit us online at
www.gardall.com



U.L. Listed
Composite Safes

Gardall Safe Corporation has been manufacturing premium quality safes for home and office applications since 1950. Our Commercial High Security safes are manufactured to specifications which are more stringent than many of our competitors requirements. Some of the standard features on Gardall TL15 and TL30 safes are options with other manufacturers. Please be sure to compare our specifications with those of our competitors before making your decision.

- **UL TL15** – Tool Resistant for 15 minutes
- **UL TL30** – Tool Resistant for 30 minutes
- **UL TL30X6** – Tool Resistant for 30 minutes all six sides of safe.

Standard Features:

Door Construction:

- TL15 – 5½" slab High Density Fiber Reinforced Material
- TL30 – 5½" overall, 3" slab of High Density Fiber Reinforced Barrier Material – TDR11*
- TL30x6 – TL30x6 – 5½" overall thickness with 2" Defense Barrier

Body Construction:

- TL15 – 2½" slab of High Density Barrier Material
- TL30 – 2½" slab of High Density Barrier Material
- TL30x6 – 2½" thick composite Reinforced Manganese steel armor plate

Anti Burglary Components:

- Cross locking relockers.
- Punch resistant spindle handle and lock.
- Tempered glass reloading trigger.
- Bridge mounted lock.
- Formed 1/8" stainless steel locking bar 1½" depth.

Locks:

- Group 2M listed combination. Key lock available for dual custody.

Hinges:

- Massive heavy duty adjustable ball bearing hinges.

Fire Rating:

- Fire tested to 1850°F. Interior temperature less than 350°F for 1 hour.

	Model	Outside Dimensions			Inside Dimensions			Approx. Cubic Ft.	Approx. Weight*	Shelves
		H	W	D	H	W	D			
TL15	1818T15	23"	23"	20¼"	18"	18"	12"	2.25	660	1
	2218T15	27"	23"	22½"	22"	18"	17"	3.9	875	1
	3822T15	43"	27"	28½"	38"	22"	20"	9.7	1440	2
	5022T15	55"	27"	28½"	50"	22"	20"	12.7	1895	3
	6222T15	67"	27"	28½"	62"	22"	20"	15.8	2350	4
TL30	1818T30	23"	23"	20¼"	18"	18"	12"	2.25	690	1
	2218T30	27"	23"	25½"	22"	18"	17"	3.9	920	1
	3822T30	43"	27"	28½"	38"	22"	20"	9.7	1530	2
	5022T30	55"	27"	28½"	50"	22"	20"	12.7	1940	3
	6222T30	67"	27"	28½"	62"	22"	20"	15.8	2300	4
	7236T30	77"	41"	28½"	72"	36"	20"	30	3430	4
TL30X6	1818T30X6	23"	23"	20½"	18"	18"	12"	2.25	850	1
	2218T30X6	27"	23"	25½"	22"	18"	17"	3.9	1125	1
	3822T30X6	43"	27"	28½"	38"	22"	20"	9.7	1960	2
	5022T30X6	55"	27"	28½"	50"	22"	20"	12.7	2400	3
	6222T30X6	67"	27"	28½"	62"	22"	20"	15.8	2840	4
	7236T30X6	77"	41"	28½"	72"	36"	20"	30	4230	4

*Add 72-100 lbs. to weight above for skid/shipping weight. All safes have bolt down holes for anchoring.