

AMVAULT TL-15 AND TL-30

AMVAULT FIRE RATED COMPOSITE SAFES



During extreme testing procedures, AMVAULT COMPOSITE SAFES demonstrated the ability to withstand severe attacks by experienced U.L. experts using powerful tools such as sledgehammers, power saws, carbide disc cutters, drills, etc., and without fail, were awarded the U.L. TL-15 and TL-30 labels.

Besides withstanding the most concentrated attacks by sophisticated burglars, each AMVAULT safe offers a Two Hour, 350° F factory fire test certification, ensuring the protection of the vault's contents against intense fires.

DOOR FEATURES

- Overall thickness of 6" and is constructed with a 3" defense barrier of outer and inner steel plates creating a single structure enclosing a unique, high density fire and burglary resistant composite material
- Defense barrier houses a proprietary amalgamation of nuggets and steel fibers to withstand concentrated attacks with the most sophisticated equipment used by burglars today
- Heavy duty pull handle standard on all CE/CF Models

BODY FEATURES

- The AmVault formed body has a total protective thickness of 3½" enclosing a high density fire resistant composite material with nuggets and steel fibers
- A reinforced drill resistant door frame protects the door and each individual bolt chamber from severe side attacks

- A proprietary inner barrier protects against peeling attacks
- High strength adjustable shelves with powder coated dark gray finish

FIRE ENDURANCE

- Two hour, 350°F factory fire rating. Tested at temperatures up to 1850°F

LOCKING MECHANISM

- Equipped with six or ten massive 1½" diameter chrome plated solid steel locking bolts. Each bolt moves deep into the body's protected bolt chambers
- Entire boltwork mechanism is also protected by a spring operated boltwork detent system. Bolts stay in the retracted position when the door is opened and automatically engage when the door is closed

THREE-WAY BOLTWORK OPTION

- Safes can be equipped with a three way active boltwork mechanism engaging the bolts horizontally and vertically into the body of the safe (except model 1814)

LOCK FEATURES

- Equipped with a U.L. listed Group 2M key changeable combination lock. The lock is protected by a massive drill shattering hard plate and two additional spring-loaded devices

HINGE FEATURES

- Offers a vertical height adjustment and utilizes an oil impregnated bearing ensuring easy door operation

OPTIONAL AUXILIARY KEY LOCK

- U.L. listed, high security auxiliary key lock is also available on all AMVAULT safes (except Model 1814). Lock is equipped with 2 keys and escutcheon cover
- An additional spring-loaded relock device protecting lock against punch attacks

OPTIONAL GLASS

RELOCKING MECHANISM

- Incorporated into the AMVAULT TL-30 auxiliary key lock is an optional high security tempered glass relock mechanism with a remotely and randomly placed "cross locking" relocking bolt and thermal cords to protect against torch attacks
- In the event of an attack by tools, torches, or explosives, the glass will shatter activating the highly sophisticated relock mechanism
- Utilizing the glass relock mechanism can offer up to a total of six different relock devices offering the ultimate in high security protection (except model 1814. Aux lock required)

OTHER OPTIONS

- Stor-It cabinets available in CE and CF models 2518, 3524, 5524, 6528, 7236
- Fully upholstered safe interior kits available for these models
- Optional premium upgrade package available. See page 10 for details

COLOR(S): Comes standard in Textured Charcoal Gray. Please refer to price book for pricing on premium colors.



CF1814



CE6528



CF7236

CF Series (TL-30)

FEATURES

- Made in the USA
- Underwriters Laboratories TL-30 rating

DOOR

- Overall thickness of 6" and is constructed with a 3" defense barrier of outer and inner steel plates creating a single structure enclosing a unique high density fire and burglary resistant material to withstand the most sophisticated attacks.

- Defense barrier houses a proprietary amalgamation of nuggets and steel fibers to withstand concentrated attacks with the most sophisticated equipment used by burglars today
- Heavy duty pull handle standard on all CF models

BODY

- 3½" thick body, also enclosing a unique high density fire and burglary resistant material to withstand the most sophisticated attacks.
- A reinforced drill resistant door frame protects the door and each individual bolt chamber from severe side attacks

- A proprietary inner barrier protects against peeling attacks
- High strength adjustable shelves

THREE-WAY BOLTWORK OPTION

- Safes can be equipped with a 3-way active boltwork mechanism engaging the bolts horizontally and vertically into the body of the safe (except model 1814)

HINGE

- Offers a vertical height adjustment and utilizes an oil impregnated bearing ensuring easy door operation

FIRE PROTECTION

- Safes withstand fires of up to 1850°F for 2 hours



CF1814



TEXTURED



Textured
Charcoal
Gray

HARDWARE



Satin



MADE IN USA

IMPORTANT:

- Add 2½" to outside depth for handle, dial and hinge projection.
- ** Model CF1814 cannot be equipped with an auxiliary lock, 3-way boltwork, or glass relock mechanism. Left swing models: After model #, use suffix "L".

Model	Outside Dimension H x W x D	Door Clearance H x W	Body Thickness	Interior Capacity	Weight	Lock Type
CF1814**	25" x 21" x 21½"	18" x 14"	3½"	1.8 cu. ft.	758 lbs.	See pg. 72
CF2518	32" x 25" x 25½"	25" x 18"	3½"	4.2 cu. ft.	1,195 lbs.	See pg. 73
CF3524	42" x 31" x 29½"	35" x 24"	3½"	9.7 cu. ft.	1,908 lbs.	See pg. 73
CF4524	52" x 31" x 29½"	45" x 24"	3½"	12.5 cu. ft.	2,311 lbs.	See pg. 73
CF5524	62" x 31" x 29½"	55" x 24"	3½"	15.3 cu. ft.	2,679 lbs.	See pg. 73
CF6528	72" x 35" x 29½"	65" x 28"	3½"	21.1 cu. ft.	3,359 lbs.	See pg. 73
CF7236	79" x 43" x 32½"	72" x 36"	3½"	34.5 cu. ft.	4,426 lbs.	See pg. 73

CE Series (TL-15)

FEATURES

- Made in the USA
- Underwriters Laboratories TL-15 rating

DOOR

- Overall thickness of 6" and is constructed with a 3" defense barrier of outer and inner steel plates creating a single structure enclosing a unique high density fire and burglary resistant material to withstand the most sophisticated attacks

- Defense barrier houses a proprietary amalgamation of nuggets and steel fibers to withstand concentrated attacks with the most sophisticated equipment used by burglars today
- Heavy duty pull handle standard on all CE models

BODY

- 3½" thick body, also enclosing a unique high density fire and burglary resistant material to withstand the most sophisticated attacks
- A reinforced drill resistant door frame protects the door and each individual bolt chamber from severe side attacks

- A proprietary inner barrier protects against peeling attacks
- High strength adjustable shelves

THREE-WAY BOLTWORK OPTION

- Safes can be equipped with a 3-way active boltwork mechanism engaging the bolts horizontally and vertically into the body of the safe (except model 1814)

HINGE

- Offers a vertical height adjustment and utilizes an oil impregnated bearing ensuring easy door operation

FIRE PROTECTION

- Safes withstand fires of up to 1850°F for 2 hours



CE2518

TEXTURED



Textured
Charcoal
Gray

HARDWARE



Chrome



MADE IN USA

IMPORTANT:

- Add 2½" to outside depth for handle, dial and hinge projection.
- ** Model CE1814 cannot be equipped with an auxiliary lock, 3-way boltwork, or glass relock mechanism. Left swing models: After model #, use suffix "L".

Model	Outside Dimension H x W x D	Door Clearance H x W	Body Thickness	Interior Capacity	Weight	Lock Type
CE1814**	25" x 21" x 21½"	18" x 14"	3½"	1.8 cu. ft.	710 lbs.	See pg. 72
CE2518	32" x 25" x 25½"	25" x 18"	3½"	4.2 cu. ft.	1,105 lbs.	See pg. 72
CE3524	42" x 31" x 29½"	35" x 24"	3½"	9.7 cu. ft.	1,674 lbs.	See pg. 72
CE4524	52" x 31" x 29½"	45" x 24"	3½"	12.5 cu. ft.	2,200 lbs.	See pg. 72
CE5524	62" x 31" x 29½"	55" x 24"	3½"	15.3 cu. ft.	2,343 lbs.	See pg. 72
CE6528	72" x 35" x 29½"	65" x 28"	3½"	21.1 cu. ft.	3,153 lbs.	See pg. 72
CE7236	79" x 43" x 32½"	72" x 36"	3½"	34.5 cu. ft.	3,880 lbs.	See pg. 72