

CF Series (TL-30)

FEATURES

- Made in the USA
- Underwriters Laboratories TL-30 rating

DOOR

- Overall thickness of 6" and is constructed with a 3" defense barrier of outer and inner steel plates creating a single structure enclosing a unique high density fire and burglary resistant material to withstand the most sophisticated attacks.

- Defense barrier houses a proprietary amalgamation of nuggets and steel fibers to withstand concentrated attacks with the most sophisticated equipment used by burglars today

- Heavy duty pull handle standard on all CF models

BODY

- 3½" thick body, also enclosing a unique high density fire and burglary resistant material to withstand the most sophisticated attacks.
- A reinforced drill resistant door frame protects the door and each individual bolt chamber from severe side attacks

- A proprietary inner barrier protects against peeling attacks
- High strength adjustable shelves

THREE-WAY BOLTWORK OPTION

- Safes can be equipped with a 3-way active boltwork mechanism engaging the bolts horizontally and vertically into the body of the safe (except model 1814)

HINGE

- Offers a vertical height adjustment and utilizes an oil impregnated bearing ensuring easy door operation

FIRE PROTECTION

- Safes withstand fires of up to 1850°F for 2 hours



CF1814



TEXTURED



Textured
Charcoal
Gray

HARDWARE



Satin



IMPORTANT:

- Add 2½" to outside depth for handle, dial and hinge projection.
- ** Model CF1814 cannot be equipped with an auxiliary lock, 3-way boltwork, or glass relock mechanism. Left swing models: After model #, use suffix "L".

Model	Outside Dimension H x W x D	Door Clearance H x W	Body Thickness	Interior Capacity	Weight	Lock Type
CF1814**	25" x 21" x 21½"	18" x 14"	3½"	1.8 cu. ft.	758 lbs.	See pg. 72
CF2518	32" x 25" x 25½"	25" x 18"	3½"	4.2 cu. ft.	1,195 lbs.	See pg. 73
CF3524	42" x 31" x 29½"	35" x 24"	3½"	9.7 cu. ft.	1,908 lbs.	See pg. 73
CF4524	52" x 31" x 29½"	45" x 24"	3½"	12.5 cu. ft.	2,311 lbs.	See pg. 73
CF5524	62" x 31" x 29½"	55" x 24"	3½"	15.3 cu. ft.	2,679 lbs.	See pg. 73
CF6528	72" x 35" x 29½"	65" x 28"	3½"	21.1 cu. ft.	3,359 lbs.	See pg. 73
CF7236	79" x 43" x 32½"	72" x 36"	3½"	34.5 cu. ft.	4,426 lbs.	See pg. 73

CE Series (TL-15)

FEATURES

- Made in the USA
- Underwriters Laboratories TL-15 rating

DOOR

- Overall thickness of 6" and is constructed with a 3" defense barrier of outer and inner steel plates creating a single structure enclosing a unique high density fire and burglary resistant material to withstand the most sophisticated attacks

- Defense barrier houses a proprietary amalgamation of nuggets and steel fibers to withstand concentrated attacks with the most sophisticated equipment used by burglars today

- Heavy duty pull handle standard on all CE models

BODY

- 3½" thick body, also enclosing a unique high density fire and burglary resistant material to withstand the most sophisticated attacks
- A reinforced drill resistant door frame protects the door and each individual bolt chamber from severe side attacks

- A proprietary inner barrier protects against peeling attacks
- High strength adjustable shelves

THREE-WAY BOLTWORK OPTION

- Safes can be equipped with a 3-way active boltwork mechanism engaging the bolts horizontally and vertically into the body of the safe (except model 1814)

HINGE

- Offers a vertical height adjustment and utilizes an oil impregnated bearing ensuring easy door operation

FIRE PROTECTION

- Safes withstand fires of up to 1850°F for 2 hours



CE2518



TEXTURED



Textured
Charcoal
Gray

HARDWARE



Chrome



MADE IN USA

IMPORTANT:

- Add 2½" to outside depth for handle, dial and hinge projection.

** Model CE1814 cannot be equipped with an auxiliary lock, 3-way boltwork, or glass relock mechanism. Left swing models: After model #, use suffix "L".

Model	Outside Dimension H x W x D	Door Clearance H x W	Body Thickness	Interior Capacity	Weight	Lock Type
CE1814**	25" x 21" x 21½"	18" x 14"	3½"	1.8 cu. ft.	710 lbs.	See pg. 72
CE2518	32" x 25" x 25½"	25" x 18"	3½"	4.2 cu. ft.	1,105 lbs.	See pg. 72
CE3524	42" x 31" x 29½"	35" x 24"	3½"	9.7 cu. ft.	1,674 lbs.	See pg. 72
CE4524	52" x 31" x 29½"	45" x 24"	3½"	12.5 cu. ft.	2,200 lbs.	See pg. 72
CE5524	62" x 31" x 29½"	55" x 24"	3½"	15.3 cu. ft.	2,343 lbs.	See pg. 72
CE6528	72" x 35" x 29½"	65" x 28"	3½"	21.1 cu. ft.	3,153 lbs.	See pg. 72
CE7236	79" x 43" x 32½"	72" x 36"	3½"	34.5 cu. ft.	3,880 lbs.	See pg. 72